

MODEL 46-1030D TRI-FUNCTION SELF-CONTAINED PRESSURE WASHER

The Model 46-1030D has been designed for the Professional Cleaner. This Pressure Washer utilizes dual clutch driven pumps that allow 10 gallons of hot water @ 3000 PSI. This product is capable of operating in three different configurations, a single gun 10 GPM @ 3000 PSI Pressure Washer, two gun 5 GPM @ 3000 PSI Pressure Washer or a single gun 5 GPM @ 3000 PSI Pressure Washer.

Note: (Single Gun Configuration Components Available As Option)

Standard Features:

- Durable Powder Coat Painted Frame
- Heavy Duty Insulated Cabinet Frame
- Forklift Pockets for Safe Easy Maneuvering
- Lockable/Removable Insulated Access Panels
- Recessed Control Panel
- Dual Adjustable Temperature Controls
- Diagnostic Controls
- Dual Output Connectors
- Amp Meter
- Hour Meter
- 32.7 HP Isuzu Diesel Engine
- Low Oil Engine Protection
- Murphy Switch Control System
- Electric Start
- Shock Absorbing Engine Base
- Plastic Battery Box
- Dual Clutch Belt Driven Pumps
- Triplex Ceramic Plunger Pumps
- Dual Pressure Relief Valve
- Thermal Pump Protection
- Dual Vertical Fuel Efficient Combustion Chambers
- Heating Coil's Constructed of 1/2" ASTM A53
- Schedule 80 Steel Pipe
- High Efficiency Beckett Pressure Atomized Burner
- Automatic Electric Burner Ignition
- Water Separating Fuel Filters
- Two 3/8" x 50' High Pressure Hose Assemblies
- Trigger Gun Control
- Two Trigger Gun and 36" Wand Assemblies
- Quick Coupled Stainless Steel Nozzles



SPECIFICATIONS:

FLOW OUTPUT (GPM)	10
PRESSURE RATING (PSI)	3000
MAXIMUM OPERATING TEMPERATURE	210
HEAT RISE DEGREES FARENHeiT	155
CLEANING COMPARISON INDEX	49,664
ENGINE HORSEPOWER	32.7
ENGINE FUEL	DIESEL
ENGINE/BURNER FUEL CAPACITY (U.S. GAL.)	36
OIL FIRED BURNER SYSTEM	
OPERATING FUEL	OIL
INPUT BTU'S	930,000
CONSUMPTION (GPH)	4
BURNER VOLTAGE	12V
STACK SIZE	TWO - 8"
DISCHARGE HOSEsS	3/8 " x 50'

DIMENSIONS

LENGTH	48"
WIDTH	48"
HEIGHT	48"
APPROXIMATE WEIGHT (LBS)	2,000